

Fuseholders 5 x 20 mm



6.3A 250Vac (max fuse rating*) T-55 to T+70 (ambient)

Maximum dissipation wattage: 1.5W

UL 94V2 UL file E92075 CSA file LR44770

These products comply with safety category PC2

*Users should be aware of the de-rating factors published by specialist manufacturers of fuses

These fuseholders are fitted with combination (solder / 2.8) mid-body terminals

It has not been possible to show both views here



M520
Terminal Cover




A0033 00
In-line 5 x 20 fuseholder
Call factory for rating details




▶ TERMINAL	▶ BODY AND CAP	▶ PANEL HOLE
<p>T</p> <p>Solder</p>	<p>0332 Finger release</p> <p>0333 Tool release</p> <p>0340 Tool release</p> <p>0341 Tool release</p>	<p>RA</p> <p>RD</p>
<p>B</p> <p>2.8 x 0.5</p>		

DIMENSIONS (mm)


0332 (T terminal shown)




0333 (T terminal shown)



0340 (T terminal shown)



0341 (T terminal shown)



Fuseholders $6 \times 30 \text{ mm}$ ($1\frac{1}{4} \times 1\frac{1}{4}$ "



16A 250Vac (max fuse rating*) T-55 to T+70 (ambient)

Maximum dissipation wattage: 2.5W

UL 94V2 UL file E92075 CSA file LR44770

These products comply with safety category PC2

*Users should be aware of the de-rating factors published by specialist manufacturers of fuses

Fuseholders with in-line termination have combination (4.8 / 6.3) terminals. It has not been possible to show both views here. Units with right angle terminals have user specified end terminals and combination mid-body terminals




M873

Cover for C & T terminals



A0035 00

In-line 6×30 $1\frac{1}{4} \times \frac{1}{4}$ fuseholder
Call factory for rating details



▶ TERMINAL	▶ BODY AND CAP	▶ PANEL HOLE	DIMENSIONS (mm)
<p>C</p> <p>6.3 x 0.8</p>	<p>0345 (C terminal shown)</p> <p>Ⓢ Ⓝ Ⓟ Ⓡ Ⓛ Ⓜ</p>	<p>RA</p> <p>16.0/16.1</p>	<p>0345 (C terminal shown)</p>
<p>D</p> <p>6.3 x 0.8 Right angle</p>	<p>0345 (D terminal shown)</p> <p>Ⓢ Ⓝ Ⓟ Ⓡ Ⓛ Ⓜ</p>	<p>Panel thickness 0.8 - 2.0mm for snap-in 0.8 - 4.5mm for nut fixing</p>	<p>0345 (D terminal shown)</p>
<p>T</p> <p>4.8 x 0.8 Solder</p>	<p>0347 (T terminal shown)</p> <p>Ⓢ Ⓝ Ⓟ Ⓡ Ⓛ Ⓜ</p>	<p>RD</p> <p>16.0/16.1</p>	<p>0347 (C terminal shown)</p>
<p>U</p> <p>4.8 x 0.8 Right angle solder</p>	<p>0347 (U terminal shown)</p> <p>Ⓢ Ⓝ Ⓟ Ⓡ Ⓛ Ⓜ</p>	<p>Panel thickness 0.8 - 2.0mm for snap-in 0.8 - 4.5mm for nut fixing</p>	<p>0347 (D terminal shown)</p>